

Roundpeg Outdoor Buildings Apex/Pent Shed Specification Sheet

Item	Specification	Included
Scandinavian Redwood	38mm x 50mm framing	✓
Cladding	12mm tongue & groove matchboard	✓
Roof & Floor	12mm finished size	✓
Fascia	Timber	✓
Felt	Heavy duty polyester non-rip felt	✓
Door – all fully framed	3' wide door with galvanised Brenton bolt and tee hinges	✓
Windows	Toughened 4mm glass, fixed, 18" x 24"	✓
Treatments	Protek quality, water-based treatment, inside and out	✓
Delivery and fitting	Monday to Friday, 8am to 4pm, fully trained and insured Roundpeg staff	✓
	Optional Extras	
Framing	50mm x 50mm framing	
	75mm x 50mm CLS framing	
Floor	16mm heavy duty, tongue and groove	
Bearers	Tanalised posts for the building to sit on, to avoid moisture being drawn from the ground into the floor.	
EPDM Rubber Roof	Firestone, 20-year guarantee with life expectancy of 50 years, pent roof only (not available on the apex roof)	
Door – all fully framed	4' double doors with galvanised Brenton bolt and tee hinges – available as 2'6" and 1'6" or 2'x2'	
	5', 6', 7' or 8' double doors with galvanised Brenton bolt and tee hinges	
	Stable door with bolts, hooks and eyes for both doors	
Windows	Toughened 4mm glass, opening, 18"x24"	
	Security windows, fixed	

Roundpeg Outdoor Buildings Apex/Pent Shed Specification Sheet

Treatments	Tanalised Timber – pressure treated timber that has been impregnated with chemicals to prevent rotting, fungal and insect infestation.	
	Factory Spray Painting using Thorndown Eco Paints. The building is first treated with a quality treatment inside and out. The exterior then has 2 coats of spray paint applied. This includes the corner trims, fascia and beading; a labour-intensive process that achieves a quality finish, not possible by hand painting.	
Fitted workbench	6' x 2'	
Shelving	Heavy duty Shelving, fitted. Single or tiers of 2 or 3	