

## Roundpeg Outdoor Buildings Garden Room Specification Sheet

| Item                    | Specification   | Included |
|-------------------------|---|----------|
| Building framing        | 75mm x 50mm CLS framing   | <b>✓</b> |
| Roof timbers            | 100mm x 50mm  | <b>√</b> |
| EPDM rubber roof        | Firestone, 1 piece with 20-year guarantee (life expectancy of 50 years)   | ✓        |
| Cladding                | 16mm (19mm nominal) Redwood tongue & groove matchboard  | <b>√</b> |
| Floor framing           | 75mm x 50mm CLS   | <b>√</b> |
| Floor                   | 16mm heavy duty, tanalised, tongue and groove   | <b>√</b> |
| Laminate flooring       | 95% waterproof, available in Alamos (mid oak), Stratos (pale grey) or Brecon Black Tile effect  | <b>√</b> |
| UPVC                    | Anthracite Grey, Black or White as standard (other colours are available) with 10-year manufacturer's guarantee + 5-year manufacturer's guarantee on the glass                  | <b>✓</b> |
| Fascia                  | UPVC colour matched to the doors and windows  | <b>√</b> |
| Bearers & front plinth  | Tanalised posts for the building to sit on, to avoid moisture being drawn from the ground into the floor, painted to match the building   | ✓        |
| Insulation              | 50mm Rockwool   | <b>√</b> |
| Membrane                | 3-layer, high quality aluminium, thermal, fire-retardant throughout   | <b>√</b> |
| Internal cladding       | 9mm moisture resistant, grooved MDF, primed white. The manufacturers recommend this is painted within 3 months of fitting   | <b>√</b> |
| Guttering/<br>downpipes | Black, round  | <b>√</b> |
| UPVC French doors       | 1235mm x 2000mm, 28mm glazed French doors with 5-point locking system   | <b>√</b> |
| Windows                 | Fixed 28mm glazed, full length UPVC, 585mm x 2000mm, other sizes are available  | <b>√</b> |
|                         | 28mm double glazed, Top Lite, UPVC on gable, the number of windows is determined by the size of the building  | <b>✓</b> |
| Paint                   | Factory Spray Painting using Thorndown Eco Paints. The building is first treated with a quality treatment inside and out. The exterior then has 2 coats of spray paint applied. | ✓        |
| External height         | 2.35m at the back and 2.45m at the front  | <b>√</b> |



## Roundpeg Outdoor Buildings Garden Room Specification Sheet

| Delivery and fitting      | Monday to Friday, fully trained and insured Roundpeg staff                                       | ✓ |
|---------------------------|--|---|
|                           | Optional Extras  |   |
| Composite cladding        | 10-year manufacturer guarantee, weather resistant, low maintenance, variety of colours available |   |
| Insulation                | 50mm PIR boards i.e Celotex – equivalent to 100mm Rockwool                                       |   |
| Laminate                  | 100% waterproof  |   |
| Doors                     | Bi fold in aluminium or UPVC, Black or Anthracite Grey   |   |
|                           | UPVC patio sliding doors   |   |
| Windows                   | Additional/different design of windows available, dependent on building size                     |   |
| Roof<br>lights/lanterns   | Various design and sizes available   |   |
| Internal factory painting | Over 20 colours available from Thorndown Paints  |   |
| Internal wood             | Contemporary oak acoustic panels – vertical or horizontal  |   |
| panels                    |  |   |
| Electrics                 | Electrical quotes can be provided and carried out by a third-party supplier                      |   |
| Base/groundwork           | Bases can be quoted for and carried out by a third-party supplier                                |   |